

Engineering Data

Wall Mounted VRF IDU



MIH15GHN18

MIH45GHN18

MIH22GHN18

MIH56GHN18

MIH28GHN18

MIH71GHN18

MIH36GHN18

MIH80GHN18

Wall Mounted

1 Specifications	4
2 Dimensions	7
3 Unit Placement	8
4 Piping Diagram.....	9
5 Wiring Diagram	10
6 Capacity Tables.....	11
7 Electrical Characteristics.....	12
8 Sound Levels	13
9 Temperature and Airflow Distributions	15

V8 VRF Indoor Units



1 Specifications

MIH15GHN18 / MIH22GHN18 / MIH28GHN18

Model			MIH15GHN18	MIH22GHN18	MIH28GHN18
Power supply			1 phase, 220-240V, 50/60Hz		
Cooling ¹	Capacity	kW	1.5	2.2	2.8
		kBtu/h	5.1	7.5	9.6
	Power input	W	18	21	24
Heating ²	Capacity	kW	1.7	2.4	3.2
		kBtu/h	5.8	8.2	10.9
	Power input	W	18	21	24
Fan motor	Model		ZKSN-20-8-5L	ZKSN-20-8-5L	ZKSN-20-8-5L
	Type		DC		
Indoor coil	Number of rows		1	1	2&3
	Fin spacing	mm	1.3	1.3	1.33
	Fin type		Hydrophilic aluminum		
	Tube OD and type	mm	Φ7 Inner-groove		Φ5 Inner-groove
	Dimensions (L×H×W)	mm	530×170×95	530×170×95	530×170×95
	Number of circuits		2	2	6
Air flow rate ³		m ³ /h	460/440/420/400/380/360/340	500/470/440/410/390/370/340	540/510/470/430/400/370/340
Sound pressure level ⁴		dB(A)	32/31/30/30/29/28/27	33/32/31/30/29/28/27	35/34/33/32/31/30/28
Unit	Net dimensions ⁵ (W×H×D)	mm	750×295×265		
	Packed dimensions (W×H×D)	mm	875×385×360		
	Net/Gross weight	kg	9/11	9/11	10/12
Refrigerant type			R410A/R32		
Throttle		Type	Electronic expansion valve		
Design pressure (H/L)		MPa	4.4/2.6		
Pipe connections	Liquid/Gas pipe	mm	Φ6.35/Φ12.7		
	Drain pipe	mm	OD Φ16		

Notes:

- Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
- Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
- Fan motor speed and air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
- Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured in an anechoic chamber.
- Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.

MIH36GHN18 / MIH45GHN18 / MIH56GHN18

Model			MIH36GHN18	MIH45GHN18	MIH56GHN18
Power supply			1 phase, 220-240V, 50/60Hz		
Cooling ¹	Capacity	kW	3.6	4.5	5.6
		kBtu/h	12.3	15.4	19.1
	Power input	W	27	30	40
Heating ²	Capacity	kW	4.0	5.0	6.3
		kBtu/h	13.6	17.1	21.5
	Power input	W	27	30	40
Fan motor	Model		ZKSN-20-8-5L	ZKSN-20-8-5L	ZKSN-20-8-5L
	Type		DC		
Indoor coil	Number of rows		2&3		
	Fin spacing	mm	1.33		
	Fin type		Hydrophilic aluminum		
	Tube OD and type	mm	Φ5 Inner-groove		
	Dimensions (L×H×W)	mm	530×170×95	730×170×95	730×170×95
	Number of circuits		6	6	6
Air flow rate ³		m ³ /h	580/540/500/460/420/380/340	720/670/620/560/510/460/410	860/780/700/620/550/480/410
Sound pressure level ⁴		dB(A)	37/36/34/33/31/30/28	37/35/33/32/31/30/29	41/39/37/35/33/31/29
Unit	Net dimensions ⁵ (W×H×D)	mm	750×295×265	950×295×265	
	Packed dimensions (W×H×D)	mm	875×385×360	1075×385×360	
	Net/Gross weight	kg	10/12	11.5/14	
Refrigerant type			R410A/R32		
Throttle		Type	Electronic expansion valve		
Design pressure (H/L)		MPa	4.4/2.6		
Pipe connections	Liquid/Gas pipe	mm	Φ6.35/Φ12.7		
	Drain pipe	mm	OD Φ16		

Notes:

- Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
- Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
- Fan motor speed and air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
- Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured in an anechoic chamber.
- Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.

V8 VRF Indoor Units



MIH71GHN18 / MIH80GHN18

Model			MIH71GHN18	MIH80GHN18
Power supply			1 phase, 220-240V, 50/60Hz	
Cooling ¹	Capacity	kW	7.1	8.0
		kBtu/h	24.2	27.3
	Power input	W	50	65
Heating ²	Capacity	kW	8.0	9.0
		kBtu/h	27.3	30.7
	Power input	W	50	65
Fan motor	Model		ZKSN-50-8-17L	ZKSN-50-8-17L
	Type		DC	
Indoor coil	Number of rows		2&3	
	Fin spacing	mm	1.33	
	Fin type		Hydrophilic aluminum	
	Tube OD and type	mm	Φ5 Inner-groove	
	Dimensions (L×H×W)	mm	980×170×95	980×170×95
	Number of circuits		8	8
Air flow rate ³		m ³ /h	1220/1120/1030/940/850/750/ 660	1380/1260/1140/1020/900/780 /660
Sound pressure level ⁴		dB(A)	58/56/54/52/50/48/46	60/57/55/53/50/48/46
Unit	Net dimensions ⁵ (W×H×D)	mm	1200×295×265	
	Packed dimensions (W×H×D)	mm	1315×385×360	
	Net/Gross weight	kg	15/18	
Refrigerant type			R410A/R32	
Throttle		Type	Electronic expansion valve	
Design pressure (H/L)		MPa	4.4/2.6	
Pipe connections	Liquid/Gas pipe	mm	Φ9.52/Φ15.9	
	Drain pipe	mm	OD Φ16	


Notes:

- Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
- Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
- Fan motor speed and air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
- Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured in an anechoic chamber.
- Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.

2 Dimensions

2.1 Unit Dimensions

Figure 2.1: Wall mounted dimensions (unit: mm)



Model(kW)	A	B	C	D	E
1.5~3.6	750	295	265	581	736
4.5~5.6	950	295	265	781	936
7.1~8.0	1200	295	265	1025	1186

V8 VRF Indoor Units

3 Unit Placement


3.1 Placement Considerations

Unit placement should take account of the following considerations:


- Units should not be installed in the following locations:
 - A place filled with mineral oil, fumes or mist, like a kitchen.
 - A place where there are corrosive gases, such as acid or alkaline gases..
 - A place exposed to combustible gases and using volatile combustible gases such as diluent or gasoline.
 - A place where there is equipment emitting electromagnetic radiation.
 - A place where there is a high salt content in the air like a coast.
 - Do not use the air conditioner in an environment where an explosion may occur.
 - Places like in vehicles or cabin rooms.
 - Factories with major voltage fluctuations in the power supplies.
 - Other special environmental conditions.
- Units should be installed in positions where:
 - Ensure that the airflow in and out of the IDU is reasonably organized to form an air circulation in the room.
 - Ensure IDU maintenance space.
 - The nearer the drainage pipe and copper pipe are to the ODU, the lower the pipe cost is.
 - Prevent the air conditioner from blowing directly to the human body.
 - The closer the wiring to the power cabinet, the lower the wiring cost is.
 - Keep the air-conditioning return air away from the setting sun of the room.
 - Be careful not to interfere with the light tank, fire pipe, gas pipe and other facilities.
 - The IDU should not be lifted in the places like load-bearing beam and columns that affect the structural safety of the house.
 - The wired controller and the IDU should be in the same installation space; otherwise, the sampling point setting of the wired controller need to be changed.

3.2 Space Requirements

Figure 3.1: Wall mounted space requirements (unit: mm)




Positioning of mounting plate:



Distance(mm) Model(kW)	A	B	C	D	E	Reserved lengths for power and signal cables	
						Left out pipe	Right out pipe
1.5~3.6	100	≥225	≥225	≥30	230	≥1115	≥415
4.5~5.6	180	≥325	≥325	≥30	412	≥1315	≥415
7.1~8.0	220	≥375	≥375	≥30	400	≥1565	≥415

4 Piping Diagram

Figure 4.1: Wall mounted piping diagram




Legend		
1	T1	Indoor ambient temperature sensor
2	T2A	Indoor heat exchanger liquid side temperature sensor
3	T2	Indoor heat exchanger mid-point temperature sensor
4	T2B	Indoor heat exchanger gas side temperature sensor

V8 VRF Indoor Units

5 Wiring Diagram

Figure 5.1: Wall mounted wiring diagram



Notes for installers and service engineers

Caution

- All installation, servicing and maintenance must be carried out by competent and suitably qualified, certified and accredited professionals and in accordance with all applicable legislation.
- Units should be grounded in accordance with all applicable legislation. Metal and other conductive components should be insulated in accordance with all applicable legislation.
- Power supply wiring should be securely fastened at the power supply terminals – loose power supply wiring would represent a fire risk.
- After installation, servicing or maintenance, the electric control box cover should be closed. Failing to close the electric control box cover risks fire or electric shock.

6 Capacity Tables

6.1 Cooling Capacity Table

Table 6.1: Wall mounted cooling capacity

Model	Indoor air temperature (°C WB/DB)													
	14/20		16/23		18/26		19/27		20/28		22/30		24/32	
	TC	SC	TC	SC	TC	SC	TC	SC	TC	SC	TC	SC	TC	SC
MIH15GHN18	1.4	1.3	1.5	1.3	1.5	1.2	1.5	1.1	1.6	1.1	1.6	1.0	1.6	0.9
MIH22GHN18	2.0	1.9	2.1	1.8	2.2	1.8	2.2	1.7	2.3	1.6	2.3	1.5	2.4	1.4
MIH28GHN18	2.5	2.2	2.7	2.3	2.8	2.2	2.8	2.1	2.9	2.0	2.9	1.8	3.0	1.7
MIH36GHN18	3.2	2.9	3.4	2.9	3.6	2.8	3.6	2.7	3.7	2.6	3.8	2.4	3.9	2.2
MIH45GHN18	4.0	3.7	4.3	3.6	4.5	3.5	4.5	3.3	4.6	3.2	4.7	2.9	4.8	2.7
MIH56GHN18	5.0	4.6	5.3	4.6	5.6	4.5	5.6	4.2	5.7	4.0	5.8	3.7	6.0	3.4
MIH71GHN18	6.3	5.8	6.7	5.7	7.0	5.6	7.1	5.3	7.2	5.1	7.4	4.6	7.6	4.3
MIH80GHN18	7.1	6.5	7.6	6.5	7.9	6.3	8.0	6.0	8.1	5.7	8.3	5.2	8.5	4.8

Abbreviations:

TC: Total capacity (kW)

SC: Sensible capacity (kW)

Notes:

1. Shaded cells indicate rating condition

6.2 Heating Capacity Table

Table 6.2: Wall mounted heating capacity

Model	Indoor air temperature (°C DB)					
	16	18	20	21	22	24
	TC	TC	TC	TC	TC	TC
MIH15GHN18	1.8	1.8	1.7	1.6	1.6	1.5
MIH22GHN18	2.6	2.6	2.4	2.3	2.3	2.1
MIH28GHN18	3.4	3.4	3.2	3.1	3.0	2.8
MIH36GHN18	4.2	4.2	4.0	3.8	3.8	3.5
MIH45GHN18	5.3	5.3	5.0	4.8	4.7	4.4
MIH56GHN18	6.7	6.6	6.3	6.1	5.9	5.5
MIH71GHN18	8.0	8.5	8.4	8.0	7.8	7.5
MIH80GHN18	9.0	9.5	9.5	9.0	8.7	8.5

Abbreviations:

TC: Total capacity (kW)

Notes:

1. Shaded cells indicate rating condition

V8 VRF Indoor Units



7 Electrical Characteristics

Table 7.1: Wall mounted electrical characteristics

Model	Power supply						Indoor fan motors	
	Hz	Volts	Min. volts	Max. volts	MCA	MFA	Rated motor output (kW)	FLA
MIH15GHN18	50/60	220-240	198	264	0.28	15	18	0.22
MIH22GHN18	50/60	220-240	198	264	0.29	15	21	0.23
MIH28GHN18	50/60	220-240	198	264	0.36	15	24	0.29
MIH36GHN18	50/60	220-240	198	264	0.39	15	27	0.31
MIH45GHN18	50/60	220-240	198	264	0.41	15	30	0.33
MIH56GHN18	50/60	220-240	198	264	0.51	15	40	0.33
MIH71GHN18	50/60	220-240	198	264	0.69	15	50	0.55
MIH80GHN18	50/60	220-240	198	264	0.98	15	65	0.78

Abbreviations:

MCA: Minimum Circuit Amps

MFA: Maximum Fuse Amps

FLA: Full Load Amps

8 Sound Levels

8.1 Overall


Table 8.1: Wall mounted sound pressure levels¹

Model name	Sound pressure levels dB(A)						
	SSH	SH	H	M	L	SL	SSL
MIH15GHN18	32	31	30	30	29	28	27
MIH22GHN18	33	32	31	30	29	28	27
MIH28GHN18	35	34	33	32	31	30	28
MIH36GHN18	37	36	34	33	31	30	28
MIH45GHN18	37	35	33	32	31	30	29
MIH56GHN18	41	39	37	35	33	31	29
MIH71GHN18	58	56	54	52	50	48	46
MIH80GHN18	60	57	55	53	50	48	46

Notes:

1. Sound pressure levels are measured in an anechoic chamber. During in-situ operation, sound pressure levels may be higher as a result of ambient noise.

Figure 8.1: Wall mounted sound pressure level measurement



8.2 Octave Band Levels

Figure 8.2: MIH15GHN18 octave band levels





Figure 8.3: MIH22GHN18 octave band levels



V8 VRF Indoor Units



Figure 8.4: MIH28GHN18 octave band levels




Figure 8.5: MIH36GHN18 octave band levels




Figure 8.6: MIH45GHN18 octave band levels




Figure 8.7: MIH56GHN18 octave band levels




Figure 8.2: MIH71GHN18 octave band levels





Figure 8.3: MIH80GHN18 octave band levels



9 Temperature and Airflow Distributions

9.1 Simulate condition

Table 9.1: Wall mounted simulate condition

Model name	Room size (m)	Ceiling height (m)	Flow angle (Cooling/Heating)	Placing
MIH15GHN18	4×4	2.7	58°/88°	Wall mounted
MIH22GHN18	4.5×4.5	2.7	58°/88°	Wall mounted
MIH28GHN18	5×5	2.7	58°/88°	Wall mounted
MIH36GHN18	5.5×5.5	2.7	58°/88°	Wall mounted
MIH45GHN18	6×6	2.7	58°/88°	Wall mounted
MIH56GHN18	8×8	2.7	58°/88°	Wall mounted
MIH71GHN18	8×8	2.7	58°/88°	Wall mounted
MIH80GHN18	8×8	2.7	58°/88°	Wall mounted

Note:

- These figures are based on software simulation. They show typical temperature and airflow distributions in the conditions above. In the actual installation, they may differ from these figures under the influence of air temperature conditions, ceiling height, cooling/heating load, obstacles, etc.

9.2 Airflow distributions (unit: m/s)

Figure 9.1: MIH15GHN18 cooling at 300S




Figure 9.2: MIH15GHN18 heating at 300S




Figure 9.3: MIH22GHN18 cooling at 300S




Figure 9.4: MIH22GHN18 heating at 300S




Figure 9.5: MIH28GHN18 cooling at 300S




Figure 9.6: MIH28GHN18 heating at 300S




Figure 9.8: MIH36GHN18 heating at 300S





Figure 9.10: MIH45GHN18 heating at 300S





Figure 9.12: MIH56GHN18 heating at 300S





Figure 9.14: MIH71GHN18 heating at 300S







Figure 9.16: MIH80GHN18 heating at 300S



9.3 Temperature distributions

Figure 9.17: MIH15GHN18 cooling at 300S




Figure 9.19: MIH22GHN18 cooling at 300S




Figure 9.21: MIH28GHN18 cooling at 300S




Figure 9.23: MIH36GHN18 cooling at 300S



Figure 9.25: MIH45GHN18 cooling at 300S




Figure 9.18: MIH15GHN18 heating at 300S




Figure 9.20: MIH22GHN18 heating at 300S




Figure 9.22: MIH28GHN18 heating at 300S





Figure 9.24: MIH36GHN18 heating at 300S



Figure 9.26: MIH45GHN18 heating at 300S



V8 VRF Indoor Units



Figure 9.27: MIH56GHN18 cooling at 300S




Figure 9.28: MIH56GHN18 heating at 300S




Figure 9.29: MIH71GHN18 cooling at 300S





Figure 9.30: MIH56GHN18 heating at 300S



Midea Building Technologies Division
Midea Group

Add.: Midea Headquarters Building, 6 Midea Avenue, Shunde, Foshan, Guangdong, China

Postal code: 528311

mbt.midea.com / global.midea.com / tsp.midea.com

Midea reserves the right to change the specifications of the product, and to withdraw or replace products without prior notification or public announcement. Midea is constantly developing and improving its products.

